



FC SOFT transfers a **very thin film that does not change the skin's natural feel** and the look of the leather. Once transferred, **the skin is ready for subsequent processing**. It needs protective resins or waxes for longer life.

DESCRIPTION:

Transfer paper for various light colored surfaces

TECHNICAL DATA:

FC SOFT is made of a 120 µm, 115 g/m² **natural paper liner**, a 30 µm, 25 g/m² **polyolefin layer** and a 4 µm **composite polymer finish**.

EQUIPMENT:

Color laser printer or copy machine + heat press

APPLICATIONS:

Excellent for **natural leather or wood**. Can be used on coated fabrics or synthetic leather.



INSTRUCTIONS:



Insert the transfer paper in the laser printer's by-pass and set to thick paper or cardboard printing mode (160-200 g/m²). Multicopy print. **Print in mirror mode.**



Place the printed side of the transfer paper on the media. Possibly protect the transfer paper with a **soft silicone mat**.



With protection

Air press: 150°C/300°F for 40 seconds - pressure 6atm

Manual press: 150°C/300°F for 40 seconds - very high pressure

Without protection

Air press: 120°C/250°F for 30 seconds - pressure 6atm

Manual press: 120°C/250°F for 30 seconds - very high pressure



Remove paper liner when **cool**

Do not machine wash. Acquires resistance to dry cleaning and excellent resistance to abrasion after appropriate tannery treatment. For further information contact your dealer.

Store in a cool dry place. Do not expose to direct sunlight. If properly stored the product will maintain its features for at least 2 years.

The instructions on this sheet are merely indicative and contain details concerning tests carried out in our laboratories with our equipment. Do your own testing. The manufacturer will replace defective material but is not responsible for any damage resulting from incorrect use.

* Available in 100 letter sheet boxes or 50 legal sheet boxes.